

CS510 | 5" 6W 100V LINE
CS610 | 6" 6W 100V LINE
CS606 | 6" 6W 100V LINE
CS343 | 4" 6W 100V LINE

SPEAKERS

DUAL CONE CEILING SPEAKER

www.amthanhtoai.vn

CS510 / CS610 : DUAL CONE CEILING SPEAKER W ABS ENCLOSURE

Available in 5" and 6" of driver size complete with matching transformer of three tappings ; 1, 3 or 6W. Back enclosure are supplied as integral part of the speakers made from quality ABS plastic. Installation is made easy with its screw mounting mechanism.

Packing information

CS510 : 850 (W) x 385 (H) x 240 (D) mm
: 15 kg
: 20 uts per carton

CS610 : 685 (W) x 475 (H) x 340 (D) mm
: 19.6 kg
: 18 uts per carton

CS606 : DUAL CONE CEILING SPEAKER W METAL ENCLOSURE

Available in 6" dual cone speaker with back metal enclosure, grill and baffle and multi tap matching transformer of 1, 3 and 6W 100V line. This model shall be suitable for installations that demand fire resistant version of dome.

Packing information

CS606 : 420 (W) x 220 (H) x 345 (D) mm
: 6.5 kg
: 6 uts per carton

CS343 : WEATHERPROOF CEILING SPEAKER

CS343 is driven by a 4" dual cone speaker with built in matching transformer of dual taps of 3 and 6W 100V line.

Made of quality ABS enclosure and aluminum grille, it is suitable for high humidity areas, such as bathrooms and salty environment. Though compact in size, it delivers satisfactory sound reproduction with high SPL level, good for listening pleasure as well as paging clarity.

Packing information

CS343 : 550 (W) x 180 (H) x 465 (D) mm
: 9.5 kg
: 9 uts per carton



TECHNICAL SPECIFICATIONS :

| | CS510 | CS610 | CS606 | CS343 |
|------------------------------|--------------------------------|--------------|-----------------------|----------------|
| SPEAKER | | | | |
| Power rating | 6W 100V line nominal (max 10W) | | | |
| Diameter | 5" (125 mm) | 6" (150 mm) | | 4" (100 mm) |
| Cone type | Dual cone | | | |
| Impedance (Ohm) | 8 | | | |
| Freq response (+/- 5dB) | 150 ~ 19 KHz | 120 ~ 19 KHz | 150 ~ 16 KHz | 150 - 18 KHz |
| SPL @ 1W / m (+/- 3dB) 1 KHz | 93 dB | 92 dB | 91 dB | 90 dB |
| Magnet weight | 3 oz | 5.3 oz | 2 oz | 3 oz |
| TRANSFORMER | | | | |
| Tapping (100V line) | 1 / 3 / 6W | | 1.5 / 3 / 6W | 3 / 6W |
| Primary impedance (Ohm) | 10 K / 3.3 K / 1.6 K | | 6.7 K / 3.3 K / 1.6 K | 3.3K / 1.67 K |
| Secondary impedance (Ohm) | 8 | | | |
| PHYSICAL | | | | |
| Grille / enclosure | White metal / ABS white | | White metal | Aluminum / ABS |
| Cutting hole dim | 140 mm | 175 mm | 165 mm | 120 mm |
| Overall size (dia x height) | 177 x 130 mm | 230 x 102 mm | 200 x 100 mm | 140 x 130 mm |
| Weight | 715 g | 785 g | 950 g | 900 g |
| Colour | White | | | |